

How-To Guide: Mass Import Substitution Entity for RFM Solutions for MDG by Utopia

Applies to

Utopia Solutions for MDG RFM

Summary

MDG for RFM include standard implementations of the Mass Import that reads the data from file which captured from other system. The data in the file can be saved to 'Active Area' directly or 'Staging Area' based on the options chosen in the Import Master Data and Mapping Information screen. The standard implementations support Key Mapping and Value Mapping.

This guide describes the necessary configuration steps for implementing Mass Import. This guide explains the Mass Import for Substitution.

You can perform most configuration tasks in Customizing for Master Data Governance under SAP Reference IMG > Cross Application Components > Processes and Tools for Enterprise Applications > Master Data Governance.

Author: Neelima Gowni

Company: Utopia Global, Inc.

Created On: November 18, 2020

Version: 1.0

Table of Contents

Introduction	3
Target Audience.....	3
Business Scenario Overview	3
General Background Information for Data Transfer.....	3
Using DIF for Article Substitution Data Overview	4
Limitation.....	4
Customizing	4
Define Object Types	4
File Source and Archive Directories	7
Setup FILE Transaction in MDG-RFM	7
Define File Source and Archive Directories for Data Transfer	8
Setup File Import Folder.....	8
Loader Class.....	10
Methods of Loader Class.....	10
LOAD Method	10
GET_INBOUND_STRUCTURE.....	10
LOG_CREATE.....	11
GET_IDoc_DATA.....	11
SET_PROXY_PERSISTANCE.....	11
CHECK_EXISTENCE_IN_ACTIVE_AREA	11
CHECK_EXISTENCE_IN_STAGING.....	12
Register.....	12
Testing Importing Class.....	12
Web Dynpro Applications	12
Export File for Article using IDocs.....	13
Import Options.....	13
Select Options on MDG_BS_FILE_IMPORT (DTIMPORT)	13
Display Monitoring	14
Scheduling File Import for MDG-RFM.....	15
Error Handling	18
Glossary	18

Introduction

This reference guide helps you understand the Mass Import of Article Master Substitution in Utopia Retail and Fashion Management (RFM) S/4HANA on Master Data Governance. This guide provides the background information about the Data Import Framework (DIF) and describes process of using DIF to upload Article data from an xml file.

Target Audience

The target audience for this guide comprises:

- Technology Consultants
- Security Consultants
- System Administrators

Business Scenario Overview

Utopia Retail and Fashion Management (RFM) extension for Master Data Governance (MDG) Retail Article (MDG-RFM) provides business processes to find, create and change Material Master data, and to mark it for deletion. It supports the governance of Article Master data on a central hub and the distribution of Article Master data to connected operational and business intelligence systems.

The processes are workflow-driven and can include several approval and revision phases, including collaboration between all users participating in master data maintenance.

You can use the Import Master Data service to import files containing Substitution data to the Master Data Governance (MDG) system. The data from these files can update existing master data records (Active Area records only), or create new ones using the options available in the Import Master Data service.

General Background Information for Data Transfer


Data transfer represents a collection of functions and features you can use to move master data and map information between the systems and the clients. Examples of the systems include existing ERP systems and your Master Data Governance hub system.

To transfer master data and mapping information, use the following steps:

1. Export the master data and mapping information from the source system to an xml file. This file is saved on your application server.
2. Copy the xml file from the application server of the source system to the application server of your target system.
3. Import the master data and mapping information to the target system using the Data Import Framework (DIF).

MDG – Generic Services Data Import Framework

The Data Import Framework is used during data load into the master data hub. Data can be loaded into the active area and into the staging area.



Using DIF for Article Substitution Data Overview

This section provides the background information about using the DIF for Article Substitution data.

Limitation

It is possible to create material master data in the Staging or Active Area. In standard, updating an existing Article Master is currently only possible in the Active Area. However, this was made possible even in Staging Area for Article Master Substitution as per the customer requirements.

Customizing

Define Object Types

- Go to Master Data Governance > General Settings > Data Transfer > Define Object Types and define the following Object Types.
 - Relationship to Business Object Type/Message Data Type
 - Implementing Classes
 - Additional Selection Fields
 - Sequence of Objects to be processed
 - Business Activity to be used in import

The customizing delivered with the solution enables you to run DIF with the SAP Standard Basic Types for Substitution (/UGI8/SUBSTITUTION). If you want to use a Custom Basic Type, you need to enhance this customizing activity.

Change View "Business Activity: Definition": Overview


New Entries

Business Activity: Definition						
Bus.Acty	Description (medium text)	D., Description (medium text)	BO Type	Description	Log. Action	Description
AD01	Display Article	AR Article Maintenance	AR_BO_ART	MDG Article	CHANGE	Change
AR01	Article Master Create	AR Article Maintenance	AR_BO_ART	MDG Article	CREATE	Create
AR02	Article Master Change	AR Article Maintenance	AR_BO_ART	MDG Article	CHANGE	Change
AR03	Article Master Display	AR Article Maintenance	AR_BO_ART	MDG Article	DISPLAY	Display
AR0A	Article Master Mass Change	AR Article Maintenance	AR_BO_ART	MDG Article	MASS	Mass Processing


- In MDGIMG customizing, define new Object Types for Data Transfer.

Note:

In this case, a new Object Type for Retail Article is provided as an example.



It is assumed that BO Type is defined earlier and assigned the same BO Type to the Retail Article Data Model. BO Type is essentially an alias to main entity in the Data Model.



- Specify the Msg. Data Type.


In Retail Article, it is expected that the /UGI8/SUBSTITUTION_01 IDoc is imported.

You can define different Msg. Data Type and assign a different Import Class.

The import class is also specified here. The import class is the main “program” that does the importing of the data.


- Set the “Active Import” checkbox.

Note: If the “Active Import” checkbox is not checked, the Object type is not displayed in the drop-down list of the import application. You can use the same import class for the different message data types (for example /UGI8/SUBSTITUTION_01).




You can maintain several and different objects to an Object Type.


It is mandatory to have the Object Type in the Object List. The sequence column determines position where the objects are appearing in the popup.



The sequence column determines the position where the objects appear in the popup as displayed in the following screen.



- Maintain the Business Activity for the Object Type. You will assign a Mass Change Business Activity.



File Source and Archive Directories

While setting up the data import, you should define source and archive logical directories in the MDG Data Transfer Customizing Activity Master Data Governance > General Settings > Data Transfer > Define File Source and Archive Directories for Data Transfer.

For more information on logical directories, see the documents for the Customizing Activity Define File Source and Archive Directories for Data Transfer.

One or more logical source directories can be defined on the application server, where files for the import may be stored. After completion of the import, the system automatically moves the processed files to the defined archive directory for the given object type.

To assign directories as source or archives:

1. The physical directory paths must first be created in the file system.
2. The SAP transaction code FILE must be used to map them to logical names. You can use these logical names in the above-mentioned Customizing activity.



Consider creating several object-specific logical directories.

You can use the SAP transaction code CG3Z to upload a file from the local file system to the application server.


Setup FILE Transaction in MDG-RFM

Use the following steps to set up FILE transaction in MDG-RFM:

1. Set up two logical paths in Transaction File
 - Path for the import files: ZMDG_FS3_RETAIL_SUBS_IMPORT
 - Path for the archive folder: ZMDG_FS3_RETAIL_ARCHIVE





2. Set up the Logical File Name Definition.
 - a. Keep <PARAM_1> for the Physical file.
 - b. Point the Logical File Name Definition to the Logical Path defined earlier.



Define File Source and Archive Directories for Data Transfer


The logical file path that was created in transaction code FILE is used. It is necessary to have an archive path for importing Object Types.



Setup File Import Folder


Use the following steps to setup the File Import folder.

1. From menu bar, click Tools > Map Network Drive.



The system displays the Map Network Driver window


2. Click Folder dropdown list and select the relevant folder



3. Click Browse. The system displays the Connect As popup.
4. Enter your credential details.



Click "OK" button. The import file folder is created. Import xml files are saved in this folder as displayed in the following screen.




Import xml files are saved into this folder.

Loader Class

Class - /UGI4/CL_MDG_FL_ART_SUBSTITUTN

/UGI4/CL_MDG_FL_ART_SUBSTITUTN was written with reference from CL_MDG_BS_FL_MATERIAL.



The importing class needs to inherit from the superclass CL_MDG_FILELOADER.

Methods of Loader Class

- [LOAD Method](#)
- [GET_INBOUND_STRUCTURE](#)
- [LOG_CREATE](#)
- [GET_IDoc_DATA](#)
- [SET_PROXY_PERSISTANCE](#)
- [CHECK_EXISTENCE_IN_ACTIVE_AREA](#)
- [CHECK_EXISTENCE_IN_STAGING](#)
- [REGISTER](#)

LOAD Method

This is the main method run by the import class to load the IDoc data into Staging or Active Area. One IDoc can contain multiple Articles.

The following important points of a loader class are listed:


- The DTIMPORT framework setting is read using the method "read_user_settings".
- One of the import parameters in this method iv_content brings in business data in xml content that is converted into various IDoc segments using method "get_idoc_data" in an external format.
- The external format data from the IDoc segments is segregated into Internal formatted IDoc segments using the methods "convert_idoc_ctrl_records" and "convert_idoc_data_records".
- The IDoc segments are looped for each control segment record nested looped for data segment records on "Docnum" key.
- Vendor Characteristics are imported to Active Area. If Governance process is chosen, and results in error, then only import to Staging Area is possible.
- It is mandatory to fill the Object keys using method call "fill_objectkeys".

GET_INBOUND_STRUCTURE

Specific structure "MDG_IDoc_DATA" maintained for IDoc is parsed in this method. This method will fetch the inbound structure from the parameter ev_name.

LOG_CREATE

The method is implemented to create log objects that can be viewed using t-code SLG0.



```

Class Builder Class /UGI4/CL_MDG_FL_ART_SUBSTITUTN Display
-----
Ty. Parameter          Typing          Description
IO_APPLICATION        TYPE REF TO CL_MDG_UPLOAD_APPL  Application Object

Method LOG_CREATE Active

1  method LOG_CREATE.
2
3      "Do create the log objects in Transaction SLG0
4
5      constants: lc_mdg_log   type balobj_d value '/UGI4/ARTICLE_UP',
6                  lc_mat_upload type balsubobj value '/UGI4/ARTICLE_UP'.
7
8      * get log helper instance to capture log for Material processing
9      call method io_application->log_create
10     exporting
11         iv_subobj   = lc_mat_upload
12         iv_log_obj  = lc_mdg_log.
13
14
15     endmethod.                                     "LOG CREATE
  
```

GET_IDoc_DATA

This method is used to convert the xml data to IDoc data.

One of the import parameters “iv_content” in Load method holds business data in xml format which is converted to various IDoc segments using this GET_IDoc_DATA method in an external format (RAW).

SET_PROXY_PERSISTANCE

This method writes Proxy Persistence to global data (1: Staging 2: Active, 3: Active with Err) which is used by standard Governance APIs to process the data.

- If user choose Persistence choice = 1, it writes to Staging or if user chooses persistence choice as 3 it writes Active Area with Errors sent to Staging.
- Data import for Vendor Characteristics is possible only to Active Area, for example, Proxy persistence equal to 2.

CHECK_EXISTENCE_IN_ACTIVE_AREA

This method checks whether the Article is present in the database (Active Area). This method uses the Function “BAPI_MATERIAL_EXISTENCECHECK” to check whether the Article referenced by the Purchase Info Record exists in Active Area.

If it exists in Active Area and if the user has not checked “Overwrite” option in DTIMPORT, the import of the Purchase Info Record will be rejected (Message 013: Article exists in Active Area; overwrite not allowed; article rejected). Otherwise if the “Overwrite” option is ticked the Article will be overridden.

The caller of this method will then the method call “USMD_MSG_TO_BAPI_MSG” to collect all the messages for Persistence option 3 (write to Active Area)


It finally calls the method “SAVE_TO_ACTIVE_AREA” that internally calls the BAPI function and writes directly to Active Area if the persistence value is set as 3.

CHECK_EXISTENCE_IN_STAGING

This method checks If Material is associated with any change request, if found it rejects the Article. It uses the method call “cl_usmd_crequest_api=>if_usmd_crequest_api~retrieve_crequest” by exporting entity, key value and data model to import CR data.

Register

The method REGISTER needs to be re-defined by registering that this class will handle the message type.



```

Class Builder Class /UGI4/CL_MDG_FL_ART_SUBSTITUTN Display
-----
Ty. Parameter Typing Descri...
CT_MDT_HANDLER TYPE TT_MDT_HANDLER


Method REGISTER Active

1 method REGISTER.
2
3 "Make sure that there is only one class that register the message data type
4
5 field-symbols <ls_mdt_handler> like line of ct_mdt_handler.
6
7 read table ct_mdt_handler assigning <ls_mdt_handler> with key mdt = gv_mdt .
8
9 if sy-subrc is initial.
10     move me to <ls_mdt_handler>-fileloader.
11 endif.
12
13 endmethod. "REGISTER
    
```

Testing Importing Class

Note that if the user uses the front-end Web Dynpro application mdg_bs_file_import to import the files, then a job is scheduled in the background. This will hinder the user for debugging the import class.

1. To test the class, set the parameter MDG_DL_DEBUG = X in your user parameters tab.



2. This parameter is read in class CL_MDG_UPLOAD_UI_ASSIST method FILE_UPLOAD. If the parameter is set, then users can put a remote breakpoint in the /UGI4/CL_MDG_FL_ART_SUBSTITUTN class to debug.

Web Dynpro Applications

In EhP6, the new Web Dynpro application MDG_BS_FILE_IMPORT (t-code DTIMPORT) is delivered.

The new Web Dynpro applications supports:

- One step process
- Aligned look and feel

- Enhanced file handling for import
- Improved mass import capabilities (allows asynchronous, scheduled and parallel processing via Web User Interface)
- Enhanced monitoring

Export File for Article using IDocs

IDoc Name: /UGI8/SUBSTITUTION

To export Article master data, you need to configure a logical system for xml-IDoc extraction to the application server file system (in each client system). To achieve this, perform the following:

1. Create a Logical System (SALE)
2. Add IDoc type /UGI8/SUBSTITUTION to Distribution Model (BD64)
3. Create an Outbound Partner Profile (WE20)
4. Create a xml-file port for IDoc processing (WE21)
5. Send Article data with transaction BD10, including Substitution data

Import Options

It is possible to perform a data import for one or more Substitution (/UGI8/SUBSTITUTION) IDoc xml files, with one or more IDocs per xml file, and with each IDoc containing one or more Articles.

Note: That the Article should already be existing to create/change the Substitution data.

The following options are available for:

- Import (Create/Change) article to Active Area with Substitution Articles.
- Import (Create/Change) article to Active Area with Substitution Articles in case of errors write to Staging
- Import (Create/Change) article to Staging Area with Substitution Articles

Select Options on MDG_BS_FILE_IMPORT (DTIMPORT)

Use the following steps to import.

1. Go to NWBC > Click on master Data Governance for RFM > Data Exchange > Data Transfer > Import Master Data.

2. Enter the details for the fields as described in the following table:

Field	Description
Object Type	Choose Article AR0A

Description	Description that helps identify import processes in the monitoring / logging
Overwrite	<ul style="list-style-type: none"> The overwrite option controls whether existing objects in the target system are overwritten. It can only be set if the IDoc will be imported to the Active Area. If you want to overwrite an Article in the Active Area, this indicator must be set. Otherwise, the import to the Active Area for an existing article will fail. If the Overwrite indicator is set, the article in the Active Area will be overwritten. If the Overwrite indicator is not set and the article is already in the Active Area, the article is rejected during import (and not written to the Staging Area). Custom Converter User defined conversion. Usually there is no additional transformation needed in this step (if the format is a SAP standard format - either IDoc or SOA based).
Governance	If activated, data is loaded into the Staging Area (a change request will be created).
Post Processing	Post processing for failed objects can be done manually (using "Forward Error Handling" or IDoc Monitoring) or can be supported by a change request process.
Change Request Type	You must select a change request type if "Governance" is set or "Post Processing defined by Change Request" is selected.
Scheduling / Date:	<ul style="list-style-type: none"> Scheduling: Indicator to determine if import is done immediately or at a scheduled date. Date: scheduling date and time
Parallel Processing / Queue Name / Number of Processes	<ul style="list-style-type: none"> Parallel Processing: indicator to determine if the import will be done with parallel processes. Queue Name: qRFC queue name which has been registered in t-code SMQ2 Number of Processes: The maximum number of parallel processes used.
Data Sources	Selection of source directories for the object types. This can be one or many per object type, and depending on the data transfer customizing, there might be main object types (for example Article) and sub object types (for example Substitution, Key Mapping, Value Mapping).
Import, Simulate Import	Starts the import process or a simulated import
Custom Converter Settings	A customer-defined converter can be leveraged by the import process. This converter can be defined and integrated in the Customizing Activity Master Data Governance > General Settings > Data Transfer > Define Filter Converter Type/BAdI: Filter dependent BAdI for file converter.

Display Monitoring

After the import has been started, you can navigate directly to the Monitoring. Web Dynpro application: MDG_BS_DL_MONITOR_CONF.

The screenshot displays the 'Import Master Data and Mapping Information' web dynpro application. At the top, there are tabs for 'Import', 'Simulate Import', 'Custom Converter Settings', and 'Display Monitoring'. The main area is divided into several sections:

- Import Settings:** Includes fields for Object Type (Retail Article - AR), Description (SUBSTITUTION), Overwrite (checked), and Custom Converter.
- Governance Settings:** Includes Governance (checked), Post Processing (Defined by Change Req), and Change Request Type (AR0A).
- Scheduling Settings:** Includes Scheduling (Import Now), Date, and Time (00:00:00).
- Parallel Processing Settings:** Includes Parallel Processing (unchecked), Queue name, and Number of Processes (0).
- Data Sources:** A table listing source directories for object types. One entry is visible: Object Type 'Article Substitution' with Source Directory 'ZMDG_FS3_RETAIL_SUBS_IMPORT'.

Scheduling File Import for MDG-RFM

Use the following steps to schedule File import for MDG-RFM:

1. Ensure that the user does not have the MDG_DL_DEBUG parameter.

Set/Get parameter ID	Parameter value	Short Description
MDG_DL_DEBUG	X	MDG Data Load Debug Mode
SCL	X	Upper and lower case in source code: 'X' = lower, '' = upper
WLC	X X XX X 00000	Workflow: User-specific settings

2. Start DTIMPORT and select Scheduling for Future Import (Select a future time).
You need at least one file in the folder before the user can schedule the import (standard MDG behavior).
3. Click Import.

Import Settings

- Object Type: Retail Article - AR
- Description: LOAD ARTICLES
- Overwrite:

Governance Settings

- Governance:
- Post Processing: Defined by Change Requi
- Change Request Type: AR0A

Scheduling Settings

- Scheduling: Import Now
- Date: [] Time: 00:00:00

Parallel Processing Settings

- Parallel Processing:
- Queue name: []
- Number of Processes: 0

Data Sources

Object Type	Source Directory
MDG Article	MDG_RETAIL_ARTICLE_IMPORT

4. Run t-code SM37 and look for the scheduled job that was created from DTIMPORT.

Simple Job Selection

Job name: [JOB_DATALOAD_IMPORT]

User name: C5108433

Job status

Sched. Released Ready Active Finished Canceled

Job start condition

From: 11.02.2014 To: 11.02.2014

or after event: []

Job step

ABAP program name: []

You can notice that there is a job JOB_DATALOAD_IMPORT released.

Job Overview

Refresh Release Spool Job log Step Application servers

Job overview from: 11.02.2014 at: : :
to: 11.02.2014 at: : :
Selected job names: *
Selected user names: C5108433

Scheduled Released Ready Active Finished Canceled
 Event controlled Event ID:
 ABAP program Program name :

JobName	Spool list	Job documentation	Job CreatedBy	Status	Start date	Start time	Duration(sec.)	Delay (sec.)
<input type="checkbox"/> ESH_FU_DEMON_010_201402111648136			C5108433	Finished	11.02.2014	17:48:13	11	0
<input type="checkbox"/> ESH_FU_DEMON_010_201402111654049			C5108433	Finished	11.02.2014	17:54:04	13	0
<input type="checkbox"/> JOB_DATALOAD_IMPORT			C5108433	Released			0	0
*Summary							24	0

5. Copy the job to a new custom job.

Job Edit Goto Extras Settings System Help

Check status Ctrl+Shift+F12
Cancel active job Ctrl+F1
Delete Shift+F2
Released -> Scheduled Shift+F6
Compare jobs Ctrl+F10
Copy Ctrl+F6
Change Ctrl+F11
Repeat scheduling Ctrl+Shift+F1
Move to different server Ctrl+Shift+F6
Capture: active job Ctrl+Shift+F7
Job details F2
Print Ctrl+P
Cancel F12

Job log Step Application servers

Active Finished Canceled

list	Job documentation	Job CreatedBy	Status	Start date	Start time	Duration(sec.)	Delay (sec.)	
<input type="checkbox"/>		C5108433	Finished	11.02.2014	17:48:13	11	0	
<input type="checkbox"/>		C5108433	Finished	11.02.2014	17:54:04	13	0	
<input checked="" type="checkbox"/>		C5108433	Released			0	0	
*Summary							24	0

Copy Job JOB_DATALOAD_IMPORT

New job name

Copy

Job Overview

Refresh Release Spool Job log Step Application servers

Job overview from: 11.02.2014 at: : :
to: 11.02.2014 at: : :
Selected job names: *
Selected user names: C5108433

Scheduled Released Ready Active Finished Canceled
 Event controlled Event ID:
 ABAP program Program name :

JobName	Spool list	Job documentation	Job CreatedBy	Status	Start date	Start time	Duration(sec.)	Delay (sec.)
<input type="checkbox"/> ESH_FU_DEMON_010_201402111648136			C5108433	Finished	11.02.2014	17:48:13	11	0
<input type="checkbox"/> ESH_FU_DEMON_010_201402111654049			C5108433	Finished	11.02.2014	17:54:04	13	0
<input type="checkbox"/> JOB_DATALOAD_IMPORT			C5108433	Released			0	0
<input checked="" type="checkbox"/>			C5108433	Scheduled			0	0
*Summary							24	0

6. After the job is copied, you can set the periodic value.

7. Save and start the job immediately.

Change Job ZMDG_JOB_DATALOAD_IMPORT

Start condition Step Job details Predecessor job Successor job(s) Job selection

General data

Job name: ZMDG_JOB_DATALOAD_IMPORT
 Job class: C
 Status: Scheduled
 Exec. Target: [] Spool list recipient

Job start | **Job frequency**

Job steps

1 Step(s) successfully defined

Start Time

Immediate Date/Time After job After event At operation mode

Immediate start

After job | At operation mode

After event

Periodic job

Check Period values Restrictions

8. You will notice that the job has been released.

Job Overview

Refresh Release Spool Job log Step Application servers

Job overview from: 11.02.2014 at: : :
 to: 11.02.2014 at: : :
 Selected job names: *
 Selected user names: C5108433

Scheduled Released Ready Active Finished Canceled
 Event controlled Event ID:
 ABAP program Program name :

JobName	Spool list	Job documentation	Job CreatedBy	Status	Start date	Start time	Duration(sec.)	Delay (sec.)
<input type="checkbox"/> ESH_FU_DEMON_010_201402111648136			C5108433	Finished	11.02.2014	17:48:13	11	0
<input type="checkbox"/> ESH_FU_DEMON_010_201402111654049			C5108433	Finished	11.02.2014	17:54:04	13	0
<input type="checkbox"/> ESH_FU_DEMON_010_201402111658085			C5108433	Finished	11.02.2014	17:58:08	11	0
<input checked="" type="checkbox"/> ZMDG_JOB_DATALOAD_IMPORT			C5108433	Released			0	0
<input type="checkbox"/> ZMDG_JOB_DATALOAD_IMPORT			C5108433	Finished	11.02.2014	17:58:07	1	0
*Summary							36	0

9. Run t-code SLG1 for any errors.

Display logs

Technical Information Help

Date/Time/User	Nu...	External ID	Object txt	Sub-object text
11.02.2014 19:31:19 WF-BATCH	1		Business Workfl...	System Job S...
11.02.2014 19:41:54 C5108433		#24/TEST	MDG_FILE_PR...	MDG_FILE_UPL...
11.02.2014 19:41:54 C5108433		#24/TEST	MDG_FILE_PR...	MDG_FILE_UPL...
11.02.2014 19:41:57 C5108433	19	CREQUEST_00...	Master Data Go...	Validation
11.02.2014 19:45:31 C5108433	3	10000425/SCH...	MDG_FILE_PR...	MDG_FILE_UPL...
11.02.2014 19:45:32 C5108433	6	10000425/SCH...	MDG_FILE_PR...	MDG_FILE_UPL...
11.02.2014 19:46:13 C5108433	20	CRequest Dele...	Master Data Go...	Deletion of Cha... S
11.02.2014 19:46:50 C5108433	3	10000426/SCH...	MDG_FILE_PR...	MDG_FILE_UPL...
11.02.2014 19:46:50 C5108433	6	10000426/SCH...	MDG_FILE_PR...	MDG_FILE_UPL...
11.02.2014 19:47:11 C5108433	20	CRequest Dele...	Master Data Go...	Deletion of Cha... S
11.02.2014 19:47:51 C5108433	3	10000427/TEST	MDG_FILE_PR...	MDG_FILE_UPL...
11.02.2014 19:49:13 C5108433	6	10000427/TEST	MDG_FILE_PR...	MDG_FILE_UPL...
11.02.2014 19:50:20 C5108433	3	10000427/TEST	MDG_FILE_PR...	MDG_FILE_UPL...
11.02.2014 19:51:20 C5108433	3	10000427/TEST	MDG_FILE_PR...	MDG_FILE_UPL...
11.02.2014 19:51:20 WF-BATCH	1		Business Workfl...	System Job S...
Problem class Additional Information	1			
11.02.2014 19:52:20 C5108433	6	10000427/TEST	MDG_FILE_PR...	MDG_FILE_UPL...
Problem class Other	6			

Ty... Message Text
 Description: TEST
 Object Type Processing Sequence: MDG Article
 Processing files from directory \\anvm100\sapmnt\trans\import\
 Message Type INFREC01 detected for file 00_ZFB030_INFREC_000000000200029.xml
 External Article ZZ026 already present in Change Request 1192 with key @@993
 Purchase Info. Record added to Change Request 1192.

Error Handling

It is possible to perform data import for one or more /UGI8/SUBSTITUTION IDoc xml files, with one or more IDocs per xml file, and with each IDoc containing one or more materials.

Scenario	No of xml Files	Import to Active Area	Import to Active Area, with errors sent to Staging Area
1 IDoc, 1 article	1 xml	If article has invalid data, import for the IDoc fails, with an error message providing what went wrong.	If article has invalid data, writing to Active Area fails and it is written to the Staging Area. An error message is displayed in log providing information on what went wrong while saving to the Active Area, along with the created change request number. If article is rejected while writing to Staging Area, an error message is displayed providing information on what went wrong.
1 IDoc and n article	1 xml	If one of the IDoc has individual data (e.g. invalid Substitution data), all the article in IDoc are rejected (all or nothing behavior of/UGI8/MDG_AR_IDoc_INPUT_SUBST). For conditions like article already present in Active Area or locked in open CR, specific article objects will be rejected, while other article objects from the IDocs are processed normally.	If one article in IDoc has invalid data (e.g. invalid Substitution Data), writing to Active Area fails and all article in IDoc are written to the Staging Area. If article is rejected by Staging Area, reject all article from the whole IDoc xml that should have been posted to Staging Area. An error message is placed providing information what went wrong.
N IDocs and 1 article each	1 xml/ IDoc	Same as row 2 – 1 IDoc n 1 Article	Same as row 2 – 1 IDoc n 1 Material
N IDoc and 1 article	1 xml for all IDoc	Data import fails for the IDoc containing the erroneous article, with error message providing information on what went wrong. Other IDocs are processed manually.	If one article in IDoc has invalid data (e.g. invalid substitution data), writing to the Active Area fails and all article in that IDoc are written to the Staging Area. If materials are rejected by the Staging Area, reject all articles from the whole IDoc xml that should have been posted to the Staging Area. An error message is displayed providing information on what went wrong.

Glossary

This section provides the list of key terms, abbreviations and acronyms.

Term/Abbreviations	Description
BOM	Bill of Material
CR	Change Request
DB	Database
EAM	Enterprise Asset Management
GW	Gateway
ICF	Internet Communication Framework
IDoc	Intermediate Document
MRO	Maintenance, Repair, and Overhaul
NW	NetWeaver
OData	Open Data Protocol
RFM	Retail and Fashion Management
t-code	SAP Transaction Code
UI	User Interface